KALLISTA.

Per Se_® Sink Faucet, Saint-Louis Crystal Knobs

P24705-CC CODES/STANDARDS APPLICABLE **FEATURES** • Solid metal construction for durability and Specified model meets or exceeds the following: reliability • ASME A112.18.1/CSA B125.1 • Two-handle, widespread lavatory faucet for • NSF 61 **CSA B651** OBC 8" (203 mm) - 16" (406 mm) centers EPA WaterSense® Quarter-turn washerless ceramic disc valves OBC* 1.2 gal/min (4.5 l/min) maximum flow rate • ST[®]LOUIS • CSA B651* • Includes Soft Touch drain • ICC/ANSI A117.1 • Thin, slender form • All applicable US Federal and State material regulations • Meets CalGreen requirements for bathroom *Compliant when installed to the specific requirement of this sink faucets regulation • Complements the Per Se collection 8" (203 mm) Min 16" (406 mm) Max 1-15/16" 5-11/16" (49 mm) 2-7/16" (144 mm) (62 mm) Т 3-1/8" 2-7/16" 1-13/16" 2-1/2" 2-1/8" (79 mm) (62 mm) (46 mm) (54 mm) (64 mm) 1-5/8" Ø 1-1/8" Ø 9/16" (41 mm) Max 2-1/8" (54 mm) 3-13/16" (97 mm) Ø 1-7/16 1/2"-14 NPSM 5-1/8" 1-1/4" OD (130 mm) Soft Touch Drain

INSTALLATION NOTES						
Mounting surface hole size. All dimensions are nominal.						
Spout	Ø 5/8" (16 mm)					
Handles	Ø 1-5/16" (33 mm)					
Deck Thickness	Min	Max				
Spout		2-1/2" (64 mm)				
Handles		1-5/8" (41 mm)				

SPECIFIED MODEL							
Model	Description	Finishes					
P24705-CC Per Se Decorative Sink Faucet, Saint-Louis Crystal Knobs	CP Polished	AD Nickel	W7 Black	24K Polished			
		Chrome	Silver	Nickel	Gold		

We reserve the right to make revisions without notice in the design of products or in packaging unless this right has specifically been waived at the time the order is accepted.